

Product Bulletin

GF 201-OAP FLEXIBLE MATTE WHITE PVC PERMANENT ADHESIVE

GF 201-OAP is a 3.4-mil premium matte white flexible calendered vinyl film coated with 200-5031 permanent gray acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems. Adhesive 200-5031 offers good opacity with low initial tack building to a permanent bond within 24 hours providing repositionability to the graphic during application. The 90# liner offers excellent product layflat in a variety of ambient conditions.

Applications	GF 201-OAP is designed for interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays.	
Thickness	Film	3.4 mils.
	Adhesive	.8 to 1.0 mils.
	Liner	6.7 mils.
	(Thickness variance +/- 10%)	
Dimensional Stability	Good.	
Temperature Ranges	Minimum application temperature	+40°F.
	Service temperature	-40°F to +180°F.
Expected Exterior Exposure	Up to 5 years.	
Adhesion	To stainless steel	40 oz/in.
Average bond	PSTC-101 Method A with 24 hr. dwell at 70°F and 50% relative humidity.	
	Typical values. Individual values may vary.	
	Test your application thoroughly.	
Water Resistance	Good. Test if immersed.	
Humidity Resistance	Good.	
Solvent Resistance	Good	
Storage Stability	6-month shelf life when stored at 70°F and 50% relative humidity.	
Product Codes	201-OAP-30	(30" x 150' roll)
	201-OAP-54	(54" x 150' roll)
	201-OAP-60	(60" x 150' roll)
Recommendations	Completely evaporate ink solvents before application. Failure to do so may facilitate solvent penetration resulting in premature vinyl degradation.	



*Manufacturers of
Pressure Sensitive Films*

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: info@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.