

Product Bulletin

GF 202 FLEXIBLE MATTE WHITE PVC REMOVABLE ADHESIVE

GF 202 is a 3.4-mil premium polymeric white matte flexible calendared vinyl film coated with 200-4982 removable acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems.

Applications	GF 202 is designed for temporary interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays. Not designed for coated/ sealed/ treated stainless steel, brass or bronze surfaces.	
Thickness	Film	3.4 mils.
	Adhesive	.8 to 1.0 mils.
	Liner	6.7 mils.
	(Thickness variance +/- 10%)	
Dimensional Stability	Good.	
Temperature Ranges	Minimum application temperature	+40°F.
	Service temperature	-40°F to +180°F.
Expected Exterior Exposure	Removable up to 1 year under normal conditions.	
Adhesion	To glass	5 to 15 oz. /in.
	To standard test panels	5 to 15 oz. /in.
	Tested according to PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.	
Water Resistance	Good. Test if immersed.	
Humidity Resistance	Good.	
Solvent Resistance	Good	
Storage Stability	6 months shelf life when stored at 70°F and 50% relative humidity.	
Product Codes	202-30	(30" X 150' roll)
	202-54	(54" X 150' roll)
	202-60	(60" X 150' roll)
Recommendations	Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation.	



**Manufacturer of Pressure Sensitive Films,
Traffic Graffice Floor Advertising Films,
Custom Coatings and Printing Inks.**

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.