Product Bulletin

GF 204

FLEXIBLE GLOSS WHITE PVC REMOVABLE ADHESIVE

GF 204 is a 3-mil premium white gloss flexible calendared vinyl film coated with 200-4982 removable acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems.

Applications GF 204 is designed for temporary interior or exterior signage, decals, nameplates, die-cut

letters and point-of-purchase displays. Not designed for coated/ sealed/ treated stainless steel,

brass or bronze surfaces.

Thickness Film 3.0 mils.

Adhesive .8 to 1.0 mils. Liner 6.7 mils. (Thickness variance +/- 10%)

Dimensional Stability Good.

Temperature Ranges Minimum application temperature is +40°F.

Service temperature is -40°F to +180°F.

Expected Exterior Exposure Removable up to 1 year under normal conditions.

Adhesion To glass 5 to 15 oz. /in.

To standard test panels 5 to 15 oz. /in.

Tested according to PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical

values. Individual values may vary. Test thoroughly before production.

Water Resistance Good

Test if immersed.

Humidity Resistance Good.

Solvent Resistance Good

Storage Stability 6 months shelf life when stored at 70°F and 50% relative humidity.

Product Codes 204-30 (30" X 150' roll) 204-54 (54" X 150' roll)

204-60 (60" X 150' roll)

RecommendationsCompletely evaporate inkjet solvents before application. Failure to do so may facilitate solvent

penetration resulting in vinyl degradation.



Manufacturers of Pressure Sensitive Films

309 S. Union ● P.O. Box 158 ● Sparta, Michigan 49345 ● (616) 887-7387 ● (800)253-3664 ● FAX (616)887-0537 Web Site: www.qeneralformulations.com ● e-mail: info@generalformulations.com