

Product Bulletin

GF 228

TransMark® - 6.0 mil Translucent Vinyl REMOVABLE ADHESIVE

GF 228 is a 6.0-mil premium translucent calendered PVC film coated with clear 200-4999 removable acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This vinyl film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems. GF 228 may be printed using other common printing processes such as UV curable screen and UV curable offset but must be tested before production.

Applications

GF 228 is premium pressure sensitive decal film with uniform light diffusion properties used to produce backlit displays for applications such as taxi tops, backlit bus displays and any other application requiring back lighting. GF 228 offers excellent bond to substrates such as polycarbonate, styrene and acrylic sheeting while maintaining easy installation and removal properties. CBS Outdoor and VeriFone taxi top approved displays.

Thickness

Film	6.0 mils.
Adhesive	.8 to 1.1 mils.
Liner	6.7 mils.
(Thickness variance +/- 10%)	

Dimensional Stability

Good.

Temperature Ranges

Minimum application temperature is +40°F.
Service temperature is -40°F to +180°F.

Expected Exterior Exposure

Removable for up to 1 year.

Adhesion

To stainless steel 16 oz/in.
PSTC-101 Method A with 24 hr. dwell at 70°F and 50% relative humidity.
Typical values. Individual values may vary. Test thoroughly before production.

Water Resistance

Excellent

Humidity Resistance

Excellent.

Solvent Resistance

Excellent

Storage Stability

One year shelf life when stored at 70°F and 50% relative humidity.

Percent Light Transmission

Approximately 20% at 550 nm.

Product Codes

228-54	(54" X 100' roll)
228-60	(60" X 100' roll)

Recommendations

Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation. Always thoroughly test this product to confirm it meets your requirements.



*Manufacturers of
Pressure Sensitive Films*

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: info@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.